

FLOWTRUE®

Water Flow Control System



Features

- Innovative flow tube cleaning mechanism
- Unique segmental valves
- Integrated non-return valve
- Modular design
- Adjustable flow meter

Benefits

- The device can be cleaned without interrupting flow and pressure to the seal
- Prevents FlowTrue® from clogging
- Protects plant water supply from product contamination
- Ensures that the device can be easily upgraded and repaired
- Controls the amount of water flowing to the mechanical seal for cooling purposes



The fully patented AESSEAL® FLOWTRUE® is a robust and adjustable flow meter that controls the amount of water flowing to the mechanical seal for cooling purposes. The unique and advanced FLOWTRUE® design means that of all the flow meters available it is the least likely to clog. This is due to large internal clearances within the design. There are three models of the FLOWTRUE® available which enables it to be used on packing applications, single seals and double mechanical seals. Additional instrumentation such as flow alarms can be added to introduce even greater control over the sealing environment.



Model FT-XX: For use with packed glands and single seals

Flow Ranges (XX):

l/min	gpm
0.5 – 1.5	0.1 – 0.4
0.5 – 3.0	0.2 – 0.8
1.0 – 8.0	0.25 – 2.0
2.0 – 15	1.0 – 4.0

All FLOWTRUE® models are available as screw connection versions (SC-shown right) as well as the push-on connection versions shown on the three models to the left.




Model FTP-XX-YYY: For use with packed glands and mechanical seals

Flow Ranges (XX):

l/min	gpm
0.5 – 1.5	0.1 – 0.4
0.5 – 3.0	0.2 – 0.8
1.0 – 8.0	0.25 – 2.0
2.0 – 15	1.0 – 4.0

Pressure Options (YYY):

bar	psi
0 – 10	0 – 145
0 – 25	0 – 360



Model FTPB-XX-YYY: For use with double mechanical seals

Flow Ranges (XX):

l/min	gpm
0.5 – 1.5	0.1 – 0.4
0.5 – 3.0	0.2 – 0.8
1.0 – 8.0	0.25 – 2.0
2.0 – 15	1.0 – 4.0

Pressure Options (YYY):

bar	psi
0 – 10	0 – 145
0 – 25	0 – 360



If you would like any more information on optional extras please contact AESSEAL® at the address below.

Barrier & buffer fluid systems for use with double mechanical seals. AESSEAL® supplies an extensive range of barrier and buffer fluid systems for use with double mechanical seals. Wherever possible AESSEAL® prefers to supply both the seal and the system. In addition the company will suggest suitable barrier or buffer fluids for most applications, based on extensive field experience. AESSEAL® accepts no responsibility for any problems associated with system design, installation, operation, or the use of an unsuitable barrier or buffer fluid, where the fluid, seal or any part of the system have not been specified and / or supplied by AESSEAL®

This document is designed to provide dimensional information and an indication of availability. For further information and safe operating limits contact our technical specialists at the locations below.



Use double mechanical seals with hazardous products. Always take safety precautions: **WARNING**

- Guard your equipment
- Wear protective clothing

UK Sales & Technical advice:
 AESSEAL plc
 Mill Close
 Bradmarsh Business Park
 Rotherham
 S60 1BZ
 United Kingdom

Tel: +44 (0) 1709 369966
 Fax: +44 (0) 1709 720788
 E-mail: seals@aes seal.com

Distributed by:

'Our purpose is to give our customers such exceptional service that they need never consider alternative sources of supply.'

www.aes seal.com

USA Sales & Technical advice:
 AESSEAL Inc.
 355 Dunavant Drive
 Rockford
 TN. 37853
 USA

Tel: +1 865 531 0192
 Fax: +1 865 531 0571
 E-mail: usa@aes seal.com

Important: Since the conditions and methods of use of this product are beyond our control, AESSEAL plc expressly disclaims any and all liability resulting or arising from any use of this product or reliance on any information contained in this document - AESSEAL plc standard conditions of sale apply. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time. AESSEAL® is a Registered Trademark of AESSEAL plc, AESSEAL plc recognizes all trademarks and trademark names as the property of their owners.