




Trapez-Pack® 619

Combination Braid of Heat Conductive ePTFE Yarn with Run In Lubricant and Stable PTFE Yarn




			
p [bar]	20	100	100
v [m/s]	20 (16*)	2	-
t °C	-100 ... +280 (200*)		
pH	1 - 14		
g/cm ³	1.70		

*practically useful data

Main areas of application:

- Pumps
- Agitators
- Blenders
- Dryers
- Filters
- Vacuum pumps



Characteristics:

- After installation TRAPEZ-PACK® turns from trapezoid into square shape providing an even pressure distribution in the entire stuffing box, avoiding outside leakage and minimising the wear of both the shaft and the packing. This extends the life of the packing and improves the sealability. It also provides short and reliable run-in periods
- 'White packing' avoids product contamination
- Wide range of use due to combination braid
- Increased life time due to mechanical resistance and good heat conductivity
- Shaft protecting (HRC25) surface is efficient
- Form stable, universal packing, suitable for vacuum

Suitable for:

- Pharmaceutical, chemical, pulp and paper, food industries

Approvals:

- FDA conformity

Form of delivery:

This packing can be manufactured from 6 to 40 mm square as well as in intermediate, inch sizes and special measurements.

10 - 15 mm on 2.5 kg spool Special length, pre-cut or die formed rings on request.
16 mm and above on 5 kg spool This packing is supplied as Style 745 in sizes smaller than 10mm in square braid.

1 kg of packing of the following cross-sections is equivalent to displayed metre lengths:

[size]	6	1/4"	8	10	7/16"	12	1/2"	14	15	16	18	19	20	22	25
[m]	37	14,6	9,2	5,9	4,9	4,08	3,65	3	2,61	2,3	1,82	1,63	1,47	1,22	0,9

All technical information and advice is based on our experience and will be given most conscientiously but without any liability. Indication and figures need to be examined by the user.
All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.