

STYLE 270

Combination braid of e-PTFE/Graphite and Para-Aramid Fibre as running surface reinforcement, contains run-in lubricant



Main areas of application:




- Pumps
- Fittings
- Refiners
- Mixers
- Kneading devices
- Agitators
- Filters

Characteristics:

- Reduced wear and excellent heat conductivity
- Recommended shaft hardness: HRC50
- Safe and universal packing for abrasive products in centrifugal pumps and other rotating equipment
- Reduces re-tightening and maintenance work

Suitable for:

- Power plants, chemical industry, in all products containing solid particles like paper and pulp industries, waste water treatment plants

			
p [bar]	25 (20*)	250	150
v [m/s]	20	2	-
t °C	-100 ... +280 (200*)		
pH	2 - 12		
g/cm ³	1.50		

*practically useful data

Form of delivery:

This packing can be manufactured from 4 to 40 mm square as well as in intermediate, inch sizes and special measurements.

04 - 09 mm on 1 kg spool Special length, pre-cut or die formed rings on request.
 10 - 15 mm on 2.5 kg spool
 16 mm and above on 5 kg spool

1 kg of packing of the following cross-sections is equivalent to displayed metre lengths:

[size]	04	05	06	1/4"	08	3/8"	10	7/16"	12	1/2"	14	15	16	18	19	20	22	25
[m]	42	27	19	16.5	10.4	7.4	6.7	5.5	4.6	4.1	3.4	3	2.6	2.1	1.9	1.7	1.4	1.1

All technical information and advice is based on our experience and will be given most conscientiously but without any liability. Indication and figures need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

AESSEAL plc
Packing Division Europe
 Rudolf-Diesel-Ring 26a
 D-82054 Sauerlach
 Germany

Telefon: +49 8104 6640-21
 Telefax: +49 8104 6640-44
 Email: packing.euro@aes seal.com
 Internet: http://www.aes seal.com

Distributed by:

Our Purpose: 'To give our customers such exceptional service that they need never consider alternative sources of supply.'